


GVS-65 & GVS-90 Gas Venting Solutions Pipe & Fittings

Rated For Maximum Flue Gas Temperatures of 65°C and 90°C.

Canadian National Price List
List No: P-GVS6590-PLV14
Effective: February 9, 2024
Replaces: March 29, 2021
All Prices are Taxes Extra



Certified to ULC S636

GVS-65 & GVS-90 Gas Venting Solutions

Please Note:

Westlake Pipe & Fittings GVS-65 and GVS-90 Gas Venting Solutions pipe and fittings must be installed according to the published installation instructions by a qualified professional.

Westlake Pipe & Fittings GVS-65 and GVS-90 components (pipe, fittings, accessories, solvent cements and primer) must be installed as a system.







DO NOT use components from other manufacturers with GVS-65 and GVS-90 components.



Certified to ULC S636








Gas Venting Solutions - GVS-65 (PVC)

GVS-65 Pipe & Fittings are white in color and rated for flue gas temperatures up to and including 65°C

Description (Pipe/Fittings)	Product Code	Alternate Code	Size (in.)	Crate (Feet)/ Carton Quantity	List Price Each (\$)
PVC Gas Vent Pipe (Certified to ULC S636, Type BH Class IIA - Maximum Temperature Rating of 65°C)					
	S40GV01510WHPE	194003	1½	1,510	\$479.00/100 ft.
	S40GV02010WHPE	194000	2	1,050	\$765.00/100 ft.
	S40GV02510WHPE	194004	2½	780	\$1,212.00/100 ft.
	S40GV03010WHPE	194001	3	580	\$1,782.00/100 ft.
	S40GV04010WHPE	194002	4	510	\$2,156.00/100 ft.
PVC Coupling (H x H) (Certified to ULC S636, Type BH Class IIA - Maximum Temperature Rating of 65°C)					
	32GVCROUP015HH	196452	1½	25	\$3.70
	32GVCROUP02HH	196352	2	70	\$4.95
	32GVCROUP025HH	196454	2½	20	\$8.80
	32GVCROUP03HH	196353	3	60	\$11.10
	32GVCROUP04HH	196354	4	30	\$19.15
PVC Long Coupling (H x H) (Certified to ULC S636, Type BH Class IIA - Maximum Temperature Rating of 65°C)					
	32GVDCOUP02HH	196453	2	20	\$8.15
	32GVDCOUP03HH	196455	3	25	\$18.40
PVC In increaser Coupling (H x H) (Certified to ULC S636, Type BH Class IIA - Maximum Temperature Rating of 65°C)					
	52GVIN01502INCHH	196362	1½ x 2	150	\$9.20
	52GVIN0203INCHH	196364	2 x 3	45	\$17.55
	52GVIN0204INCHH	196365	2 x 4	30	\$23.10
	52GVIN0304INCHH	196366	3 x 4	30	\$26.50
PVC Reducer Bushing (H x Sp) (Certified to ULC S636, Type BH Class IIA - Maximum Temperature Rating of 65°C)					
	52GVIN05015INCHS	196653	½ x 1½	160	\$3.30
	52GVIN01502INCHS	196282	1½ x 2	80	\$4.40
	52GVIN015025INCHS	196666	1½ x 2½	60	\$7.90
	52GVIN02025INCHS	196667	2 x 2½	60	\$8.35
	52GVIN0203INCHS	196284	2 x 3	50	\$8.65
	52GVIN02503INCHS	196673	2½ x 3	20	\$9.30
PVC Hex Head Reducer Bushing (H x Sp) (Certified to ULC S636, Type BH Class IIA - Maximum Temperature Rating of 65°C)					
	52GVHHIN0203INCHS	196672	2 x 3	20	\$19.25






Gas Venting Solutions - GVS-65 (PVC)

GVS-65 Pipe & Fittings are white in color and rated for flue gas temperatures up to and including 65°C

Description (Pipe/Fittings)	Product Code	Alternate Code	Size (in.)	Crate (Feet)/ Carton Quantity	List Price Each (\$)
PVC 90° Elbow (H x H) (Certified to ULC S636, Type BH Class IIA - Maximum Temperature Rating of 65°C)					
	26GV9002HH	196035	2	50	\$8.40
	26GV90025HH	196525	2½	10	\$17.70
	26GV9003HH	196025	3	25	\$22.65
PVC 90° Elbow (H x Sp) (Certified to ULC S636, Type BH Class IIA - Maximum Temperature Rating of 65°C)					
	26GV9002HS	196232	2	60	\$7.30
	26GV9003HS	196233	3	15	\$20.65
PVC 90° Long Elbow (H x H) (Certified to ULC S636, Type BH Class IIA - Maximum Temperature Rating of 65°C)					
	25GVL90015HH	196121	1½	120	\$6.80
	25GVL9002HH	196122	2	55	\$8.65
	25GVL9003HH	196123	3	23	\$22.60
	25GVL9004HH	196124	4	20	\$45.30
PVC 90° Extra Long Elbow (H x H) (Certified to ULC S636, Type BH Class IIA - Maximum Temperature Rating of 65°C)					
	25GV9002HH	196022	2	40	\$9.15
	25GV9003HH	196023	3	15	\$23.90
PVC 45° Elbow (H x H) (Certified to ULC S636, Type BH Class IIA - Maximum Temperature Rating of 65°C)					
	26GV45015HH	196241	1½	175	\$4.75
	26GV4502HH	196242	2	110	\$7.20
	26GV45025HH	196487	2½	10	\$16.00
	26GV4503HH	196243	3	25	\$19.55
	26GV4504HH	196244	4	20	\$34.15
PVC 45° Elbow (H x Sp) (Certified to ULC S636, Type BH Class IIA - Maximum Temperature Rating of 65°C)					
	26GV4502HS	196071	1½	50	\$8.80
PVC 45° Long Turn Elbow (H x H) (Certified to ULC S636, Type BH Class IIA - Maximum Temperature Rating of 65°C)					
	25GVL4502HH	196010	2	45	\$8.40
	25GVL4503HH	196011	3	20	\$21.75







Gas Venting Solutions - GVS-65 (PVC)

GVS-65 Pipe & Fittings are white in color and rated for flue gas temperatures up to and including 65°C

Description (Pipe/Fittings)	Product Code	Alternate Code	Size (in.)	Crate (Feet)/ Carton Quantity	List Price Each (\$)
PVC 22½° Elbow (H x H) (Certified to ULC S636, Type BH Class IIA - Maximum Temperature Rating of 65°C)					
	26GV2202HH	196252	2	45	\$12.45
PVC Sanitary Tee (H x H X H) (Certified to ULC S636, Type BH Class IIA - Maximum Temperature Rating of 65°C)					
	06GV015015015HHH	196081	1½	110	\$9.30
	06GV02020202HHH	196082	2	35	\$14.55
	06GV025025025HHH	196781	2½	10	\$21.65
	06GV0202015HHH	196056	2 x 1½	40	\$11.90
	06GV030303HHH	196083	3	17	\$26.00
	06GV0303015HHH	196061	3 x 1½	30	\$25.50
	06GV030302HHH	196822	3 x 2	10	\$32.20
	06GV040404HHH	196084	4	5	\$41.00
	06GV040402HHH	196828	4 x 2	5	\$53.55
PVC Female Adapter (H x FPT) (Certified to ULC S636, Type BH Class IIA - Maximum Temperature Rating of 65°C)					
	18GV0202HFPT	196564	2	20	\$7.10
PVC Hose Barb (Sp x B) (Certified to ULC S636, Type BH Class IIA - Maximum Temperature Rating of 65°C)					
	94GVHB01505SB	196278	1½ x ½	80	\$4.40
PVC Test Bushing c/w Plug (Sp x FPT) (Certified to ULC S636, Type BH Class IIA - Maximum Temperature Rating of 65°C)					
	94GVTB0205SFPT	196143	2 x ½	10	\$17.00

Gas Venting Solutions - GVS-90 (CPVC)

GVS-90 Pipe & Fittings are grey in color and rated for flue gas temperatures up to and including 90°C


Description (Pipe/Fittings)	Product Code	Alternate Code	Size (in.)	Crate (Feet)/ Carton Quantity	List Price Each (\$)
CPVC Gas Vent Pipe (Certified to ULC S636, Type BH Class IIB - Maximum Temperature Rating of 90°C)					
	S40CPVCGV01510GYPE	198003	1½	1,510	\$1,663.00/100 ft.
	S40CPVCGV02010GYPE	198001	2	1,050	\$2,184.00/100 ft.
	S40CPVCGV02510GYPE	198004	2½	780	\$3,460.00/100 ft.
	S40CPVCGV03010GYPE	198000	3	580	\$4,505.00/100 ft.
	S40CPVCGV04010GYPE	198002	4	510	\$6,404.00/100 ft.
	S40CPVCGV06010GYPE	198005	6	260	\$8,754.00/100 ft.
CPVC Coupling (H x H) (Certified to ULC S636, Type BH Class IIB - Maximum Temperature Rating of 90°C)					
	32GVFCOUP015HH	197136	1½	10	\$9.60
	32GVFCOUP02HH	197137	2	10	\$13.60
	32GVFCOUP025HH	197138	2½	5	\$25.15
	32GVFCOUP03HH	197139	3	5	\$33.85
	32GVFCOUP04HH	197023	4	5	\$46.30
	32GVFCOUP06HH	197141	6	5	\$142.00
CPVC Increaser Coupling (H x H) (Certified to ULC S636, Type BH Class IIB - Maximum Temperature Rating of 90°C)					
	52GVFIN0203INCHH	197470	3 x 2	5	\$45.70
	52GVFIN0304INCHH	197472	4 x 3	5	\$75.00
CPVC Hex Head Reducer Bushing (H x Sp) (Certified to ULC S636, Type BH Class IIB - Maximum Temperature Rating of 90°C)					
	52GVFIN0502INCHS	197385	½ x 2	80	\$9.90
	52GVFIN07502INCHS	197386	¾ x 2	10	\$10.75
	52GVFIN01502INCHS	197389	1½ x 2	10	\$11.15
	52GVFIN0203INCHS	197394	2 x 3	10	\$25.65
	52GVFIN02503INCHS	197395	2½ x 3	10	\$26.45
	52GVFIN0204INCHS	197396	2 x 4	20	\$44.15
	52GVFIN0406INCHS	197400	4 x 6	10	\$168.00
CPVC 90° Elbow (H x H) (Certified to ULC S636, Type BH Class IIB - Maximum Temperature Rating of 90°C)					
	26GVF9002HH	197199	2	15	\$24.25
	26GVF9003HH	197201	3	5	\$62.00
	26GVF9004HH	197202	4	5	\$111.00
	26GVF9006HH	197203	6	5	\$244.00
CPVC 90° Long Elbow (H x H) (Certified to ULC S636, Type BH Class IIB - Maximum Temperature Rating of 90°C)					
	25GVFL9002HH	197122	2	55	\$18.55
	25GVFL9003HH	197123	3	23	\$46.25
	25GVFL9004HH	197124	4	20	\$85.00
	25GVFL9006HH	197125	6	5	\$274.00

Gas Venting Solutions - GVS-90 (CPVC)


GVS-90 Pipe & Fittings are grey in color and rated for flue gas temperatures up to and including 90°C

Description (Pipe/Fittings)	Product Code	Alternate Code	Size (in.)	Crate (Feet)/ Carton Quantity	List Price Each (\$)
--------------------------------	-----------------	-------------------	---------------	----------------------------------	-------------------------


CPVC 45° Elbow (H x H) (Certified to ULC S636, Type BH Class IIB - Maximum Temperature Rating of 90°C)

	26GVF4502HH	197169	2	10	\$18.85
	26GVF4503HH	197171	3	5	\$52.40
	26GVF4504HH	197172	4	5	\$85.00
	26GVF4506HH	197173	6	5	\$210.00


CPVC Tee (H x H x H) (Certified to ULC S636, Type BH Class IIB - Maximum Temperature Rating of 90°C)

	09GVF020202HHH	197486	2	10	\$34.10
	09GVF030303HHH	197488	3	5	\$75.00
	09GVF030302HHH	197502	3 x 2	5	\$66.00
	09GVF040404HHH	197489	4	5	\$103.00
	09GVF040402HHH	197504	4 x 2	5	\$111.00
	09GVF060606HHH	197490	6	4	\$360.00
	09GVF060604HHH	197506	6 x 4	4	\$330.00


CPVC Female Adapter (H x FPT) (Certified to ULC S636, Type BH Class IIB - Maximum Temperature Rating of 90°C)

	18GVF0202HFPT	197224	2	10	\$15.15


CPVC Hose Barb (Sp x B) (Certified to ULC S636, Type BH Class IIB - Maximum Temperature Rating of 90°C)

	94GVFHB01505SB	197278	½ x 1½	80	\$9.75








CPVC Test Bushing c/w Plug (Sp x FPT) (Certified to ULC S636, Type BH Class IIB - Maximum Temperature Rating of 90°C)

	94GVFTB0205SFPT	197143	2	10	\$39.20

CPVC Condensate Drain Assembly (Sp x FPT) (Certified to ULC S636, Type BH Class IIB - Maximum Temperature Rating of 90°C)

	94GVF0504CDAFS	197002	½ x 4	1	\$155.00
	94GVF0506CDAFS	197003	½ x 6	1	\$278.00


Gas Venting Solutions - Accessories

Description (Pipe/Fittings)	Product Code	Alternate Code	Size (in.)	Crate (Feet)/ Carton Quantity	List Price Each (\$)
GVS-65 PVC Concentric Vent Kits (Certified to ULC S636, Type BH Class IIA - Maximum Temperature Rating of 65°C)					
	52CVKGV6502	196005	2 x 16	1	\$178.00
	52CVKGV6502-28	196105	2 x 28	1	\$204.00
	52CVKGV6502-40	196125	2 x 40	1	\$220.00
	52CVKGV6503	196006	3 x 20	1	\$239.00
	52CVKGV6503-32	196106	3 x 32	1	\$260.00
	52CVKGV6503-44	196116	3 x 44	1	\$280.00
	52CVKGV6504	196021	4 x 36	1	\$560.00
GVS-90 CPVC Concentric Vent Kits (Certified to ULC S636, Type BH Class IIB - Maximum Temperature Rating of 90°C)					
	52CVKGV9003	197009	3 x 20	1	\$425.00
	52CVKGV9003-32	197107	3 x 32	1	\$460.00
	52CVKGV9003-44	197117	3 x 44	1	\$491.00
	52CVKGV9004-36	197021	4 x 36	1	\$1,002.00
GVS-65 PVC Wall Vent Kits (Certified to ULC S636, Type BH Class IIA - Maximum Temperature Rating of 65°C)					
	52WTVKGV6502	081216	2	1	\$150.00
	52WTVKGV65025	081218	2½	1	\$220.00
	52WTVKGV6503	081219	3	1	\$249.00
GVS-65 PVC Side Wall Vent Kits (Certified to ULC S636, Type BH Class IIA - Maximum Temperature Rating of 65°C)					
	52SWVKGV6502	196984	2	1	\$72.00
	52SWVKGV6503	196985	3	1	\$72.00
GVS-65 PVC Faceplate (Round - Self Foam Back - White)					
	94GVWHTROUFP02	196063	2	65	\$28.10
	94GVWHTROUFP03	196064	3	65	\$34.65
	94GVWHTROUFP04	196055	4	65	\$40.50
GVS-90 CPVC Faceplate (Round - Self Foam Back - Grey)					
	94GVGRYROUFP02	197053	2	65	\$27.65
	94GVGRYROUFP03	197054	3	65	\$33.55
	94GVGRYROUFP04	197055	4	65	\$38.55
GVS-65 PVC Faceplate (Rectangular - Self Foam Back - White)					
	94GVWHTRECTFP02	196216	2	65	\$48.95
	94GVWHTRECTFP025	196218	2½	65	\$50.00
	94GVWHTRECTFP03	196219	3	65	\$49.35


Gas Venting Solutions - Accessories

Description (Pipe/Fittings)	Product Code	Alternate Code	Size (in.)	Crate (Feet)/ Carton Quantity	List Price Each (\$)
--------------------------------	-----------------	-------------------	---------------	----------------------------------	-------------------------





Termination Vent Screens

	99GV02SCREEN	196050	2	250	\$6.45
	99GV03SCREEN	196051	3	100	\$16.20
	99GV04SCREEN	196052	4	75	\$19.45
	99GV06SCREEN	196090	6	5	\$33.60

Deburring Tools

	99GVDEBT00L01503	196049	1/2 - 3 Pipe	6	\$130.10
	99GVDEBT00L04	196048	4 Pipe	6	\$156.40

Gas Venting Solutions - Cements

Description (Pipe/Fittings)	Product Code	Alternate Code	Size (in.)	Crate (Feet)/ Carton Quantity	List Price Each (\$)
GVS-65 PVC Solvent Cement (ULC S636 Listed for use with GVS-65 Products)					
	RCC40-500ML	196040	475 ml (Grey)	12	\$24.05
	RCC40-1LT	196041	950 ml (Grey)	12	\$40.00
GVS-65 PVC and GVS-90 CPVC Primer (ULC S636 Listed for use with GVS-65 and GVS-90 Products)					
	RCP40-500ML	196042	475 ml (Purple)	12	\$27.35
	RCP40-1LT	196043	950 ml (Purple)	12	\$43.90
	RCP40CL-500ML	196017	475 ml (Clear)	12	\$29.85
	RCP40CL-1LT	-	950 ml (Clear)	12	\$50.20
GVS-65 and GVS-90 PVC/CPVC/ABS Transition Cement					
	RCCABS-PVC500ML	196044	475 ml (White)	12	\$27.30
	RCCABS-PVC1LT	-	950 ml (White)	12	\$42.50
GVS-90 CPVC Solvent Cement (ULC S636 Listed for use with GVS-90 Products)					
	RCC41-500ML	196046	475 ml (Orange)	12	\$33.30
	RCC41-1LT	196047	950 ml (Orange)	12	\$68.00

Note: Westlake Pipe & Fittings Solvent Cements packaged in metal containers have a shelf-life of 24 months from the date of manufacture.

Westlake Pipe & Fittings Primers and Cleaners packaged in metal containers have a shelf-life of 36 months from the date of manufacture.